



# NIMMO

## LED FLOODLIGHT RANGE

### REPLACING 50W TO 2000W FLOOD LIGHTS



To see 360 degree rotations of this product visit [littil.com.au](http://littil.com.au)

### APPLICATIONS

Waterproof LED Flood Light in 10W-1,000W, a direct replacement for the energy consuming 50W-2,000W Metal Halide Flood Lamps.

Zero radiation or interference, this high powered lamp is perfect for commercial applications such as sports grounds and stadiums.

### FEATURES & BENEFITS

- High performance pipe efficiently dissipates heat
- Waterproof respirator – avoids fogging and condensation
- Long 1m flex cable for easy installation

	10W	20W	30W	50W	70W	100W	150W	200W	400W	500W	1000W
--	-----	-----	-----	-----	-----	------	------	------	------	------	-------

### GENERAL

Model Number	FL-10W-02	FL-20W-02	FL-30W-02	FL-50W-02	FL-70W-02	FL-100W-02	FL-150W-02	FL-200W-02	FL-400W-02	FL-500W-02	FL-1000W-02
Dimensions (mm)	159 x 132 x 53	203 x 176 x 64	219 x 191 x 64	282 x 220 x 113	282 x 220 x 117	310 x 268 x 182	365 x 298 x 187	465 x 344 x 197	436 x 416 x 300	439 x 419 x 337	534 x 436 x 497
Category	Floodlights										
Lifetime	50,000 hrs										
IP Rating	IP65										
Warranty	5 years										
Operating Temperature	45°C										

### OPTICAL

Output (Lms)	775 Lms	1799 Lms	2632 Lms	4532 Lms	6388 Lms	9125 Lms	13660 Lms	18863 Lms	40000 Lms	50000 Lms	100000 Lms
LED Type	Epistar							CREE			
LED Colour Temperature	3000K*, 4000K*, 5000K, 6000K*										
Full Beam Angle	120°							25°, 45°, 60°, 90°, 100°		90° x 10 90° x 50	
CRI	>80										

### ELECTRICAL

Voltage	100-240 VAC, 50/60 Hz										
Power Factor	0.9										
Dimming	Non-Dimmable										

### OPTIONS

Lens	Clear										Frosted
Trim	Black										

### COMPLIANCE



\*Available as custom order

Luminous Intensity Distribution

